

## SAFETY DATA SHEET

# Isfjerner CL-123

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

#### ▼ Trade name

Isfjerner CL-123

#### Unique formula identifier (UFI)

P7DA-WVHJ-5T0C-U3FR

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses of the substance or mixture

Industrial purposes

#### Use descriptors (REACH)

Sectors of use	Description
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
LCS "C"	Consumer uses: Private households (= general public = consumers)
Product category	Description
PC 35	Washing and Cleaning Products (including solvent based products)
Environmental release category	Description
ERC 8a	Wide dispersive indoor use of processing aids in open systems

#### Uses advised against

None known.

### 1.3. Details of the supplier of the safety data sheet

#### ▼ Company and address

**Pureno A/S**

Gefionsvej 20

3400 Hillerød

Denmark

+45 70 260 267

#### ▼ Contact person

Lars Skaarup

#### ▼ E-mail

ls@pureno.dk

#### Revision

07/10/2024

#### SDS Version

3.0

#### Date of previous version

10/11/2022 (2.0)

### 1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)

See section 4 "First aid measures".

## SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP).

### 2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2; H319, Causes serious eye irritation.

### 2.2. Label elements

## Hazard pictogram(s)



## Signal word

Danger

## Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)  
Causes serious eye irritation. (H319)

## Precautionary statement(s)

## General

Keep out of reach of children. (P102)  
If medical advice is needed, have product container or label at hand. (P101)

## Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)  
Do not pierce or burn, even after use. (P251)  
Do not spray on an open flame or other ignition source. (P211)

## Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing. (P305+P351+P338)  
If eye irritation persists: Get medical advice/attention. (P337+P313)

## Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

## Disposal

-

## Hazardous substances

None known.

## Additional labelling

UFI: P7DA-WVHJ-5T0C-U3FR

## 2.3. Other hazards

## ▼ Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.  
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.  
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

## SECTION 3: Composition/information on ingredients

## 3.1. ▼ Substances

Not applicable. This product is a mixture.

## 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 REACH: 01-2120063206-63-XXXX Index No.: 603-002-00-5	60-80%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 (SCL: 50.00 %)	
propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: Index No.: 603-117-00-0	5-10%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
carbon dioxide	CAS No.: 124-38-9 EC No.: 204-696-9 REACH: Index No.:	5-10%	Press. Gas (Liq.) , H280	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

## Other information

[1] European occupational exposure limit.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

#### ▼ Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

#### ▼ Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

#### Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure. Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

### 4.3. ▼ Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

#### Information to medics

Bring this safety data sheet or the label from this product.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

### 5.3. ▼ Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the chemical emergency services on 72 85 20 00 (24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

### 6.3. ▼ Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. ▼ Precautions for safe handling

Avoid static electricity.

Protect electrical equipment in accordance with current standards. To divert static electricity during transmission, containers must be grounded and connected by wire with the receiving containers. Do not use spark-forming tools.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Storage conditions

> 0°C

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. ▼ Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. ▼ Control parameters

ethanol

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1900

Long term exposure limit (8 hours) (ppm): 1000

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 3800

Short term exposure limit (15 minutes) (ppm): 2000

propan-2-ol;isopropyl alcohol;isopropanol

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 490

Long term exposure limit (8 hours) (ppm): 200

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 980

Short term exposure limit (15 minutes) (ppm): 400

carbon dioxide

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 9000

Long term exposure limit (8 hours) (ppm): 5000

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 18000

Short term exposure limit (15 minutes) (ppm): 10000

Annotations:

E = Substance has an EC limit.

Statutory order 291 on exposure limits for substances and mixtures (19/03/2024)

## ▼ DNEL

ethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	206 mg/kg legemsvægt pr. dag
Long term – Systemic effects - General population	Dermal	206 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	343 mg/kg legemsvægt pr. dag
Long term – Systemic effects - Workers	Dermal	343 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	114 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	114 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	950 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	380 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	950 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	950 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	1900 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	1900 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	87 mg/kg legemsvægt pr. dag
Long term – Systemic effects - General population	Oral	87 mg/kg bw/day

propan-2-ol;isopropyl alcohol;isopropanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319mg/kg bw/dag
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/dag
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	89 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	500 mg7m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	500 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	178 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	1000 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	26mg/kg bw/dag
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
Short term – Systemic effects - General population	Oral	51 mg/kg bw/day

## ▼ PNEC

ethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0,96 mg/l
Freshwater		960 µg/L

Freshwater sediment	3,6 mg/kg
Freshwater sediment	3.6 mg/kg
Intermittent release	2,75 mg/l
Intermittent release (freshwater)	2.75 mg/L
Marine water	0,79 mg/l
Marine water	790 µg/L
Marine water sediment	2,9 mg/kg
Marine water sediment	2.9 mg/kg
Predators	380-720 mg/kg
Sewage treatment plant	580 mg/l
Sewage treatment plant	580 mg/L
Soil	0,63 mg/kg
Soil	630 µg/kg

propan-2-ol;isopropyl alcohol;isopropanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140,9 mg/l
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Freshwater sediment		552 mg/kg
Intermittent release		140,9 mg/l
Intermittent release (freshwater)		140.9 mg/L
Marine water		140,9 mg/l
Marine water		140.9 mg/L
Marine water sediment		552mg/kg
Marine water sediment		552 mg/kg
Predators		160 mg/kg
Sewage treatment plant		251 mg/l
Sewage treatment plant		2.251 g/L
Soil		28 mg/kg
Soil		28 mg/kg

## 8.2. ▼ Exposure controls

Apply general control to prevent unnecessary exposure

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### ▼ Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

### Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

### ▼ Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

### Measures to avoid environmental exposure

No specific requirements.

## Individual protection measures, such as personal protective equipment

### Generally

Use only CE marked protective equipment.

### Respiratory Equipment

Work situation	Type	Class	Colour	Standards
When developing vapour, use respiratory protection with approved filter	Normally, personal respiratory equipment is not necessary			

## Skin protection

Recommended	Type/Category	Standards
No special when used as intended	-	-

## Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
No special when used as intended	-	-	-

## Eye protection

Type	Standards
Safety glasses	EN166



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Aerosol

#### Colour

Clear

#### Odour / Odour threshold

Alcohol odor

#### ▼ pH

No relevant or available data due to the nature of the product.

#### Density (g/cm<sup>3</sup>)

0.9

#### ▼ Kinematic viscosity

No relevant or available data due to the nature of the product.

#### ▼ Particle characteristics

No relevant or available data due to the nature of the product.

#### Phase changes

#### ▼ Melting point/Freezing point (°C)

No relevant or available data due to the nature of the product.

#### Softening point/range (°C)

Does not apply to aerosols.

#### Boiling point (°C)

1

#### ▼ Vapour pressure

No relevant or available data due to the nature of the product.

#### ▼ Relative vapour density

No relevant or available data due to the nature of the product.

#### ▼ Decomposition temperature (°C)

No relevant or available data due to the nature of the product.

#### Data on fire and explosion hazards

#### Flash point (°C)

14

#### ▼ Flammability (°C)

The material is ignitable.

#### ▼ Auto-ignition temperature (°C)

No relevant or available data due to the nature of the product.

## ▼ Lower and upper explosion limit (% v/v)

No relevant or available data due to the nature of the product.

## Solubility

### ▼ Solubility in water

No relevant or available data due to the nature of the product.

### ▼ n-octanol/water coefficient (LogKow)

No relevant or available data due to the nature of the product.

### ▼ Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

## 9.2. Other information

### Other physical and chemical parameters

No data available.

### ▼ Oxidizing properties

No relevant or available data due to the nature of the product.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### ▼ Acute toxicity

Product/substance	ethanol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	10470 mg/kg ·

Product/substance	ethanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>17100 mg/kg ·

Product/substance	ethanol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	124,7 mg/l ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg ·

Product/substance	propan-2-ol;isopropyl alcohol;isopropanol
Species:	Rat
Route of exposure:	Oral



Test: LD50  
Result: 5840 mg/kg ·

Product/substance: propan-2-ol;isopropyl alcohol;isopropanol  
Species: Rat  
Route of exposure: Inhalation  
Test: LC50  
Result: 66,1mg/l 4 h ·

Product/substance: propan-2-ol;isopropyl alcohol;isopropanol  
Species: Rat  
Route of exposure: Inhalation  
Test: LC50  
Result: 47,5mg/l 8 h ·

Product/substance: carbon dioxide  
Species: Rat  
Route of exposure: Inhalation  
Test: LC50  
Result: 470000 ppm 0,5 h ·

## Skin corrosion/irritation

Based on available data, the classification criteria are not met.

## Serious eye damage/irritation

Causes serious eye irritation.

## Respiratory sensitisation

Based on available data, the classification criteria are not met.

## Skin sensitisation

Based on available data, the classification criteria are not met.

## Germ cell mutagenicity

Based on available data, the classification criteria are not met.

## Carcinogenicity

Based on available data, the classification criteria are not met.

## Reproductive toxicity

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

## Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

### ▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

### ▼ Other information

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

## SECTION 12: Ecological information

### 12.1. ▼ Toxicity

Product/substance: ethanol  
Species: Fish  
Duration: 48 hours  
Test: LC50

Result: 8150 mg/l ·

Product/substance ethanol  
Species: Fish  
Duration: 96 hours  
Test: LC50  
Result: 1100 mg/l ·

Product/substance ethanol  
Species: Daphnia  
Duration: 48 hours  
Test: EC50  
Result: 9268-14221 mg/l ·

Product/substance ethanol  
Species: Algae  
Duration: 7 days  
Test: EC0  
Result: 5000 mg/l ·

Product/substance ethanol  
Species: Crustacean  
Duration: 16 hours  
Test: EC0  
Result: 6500 mg/l ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol  
Species: Algae  
Duration: 8 days  
Test: NOEC  
Result: >1800 mg/l ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol  
Species: Fish  
Duration: 96 hours  
Test: LC50  
Result: 8970-9280 mg/l ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol  
Species: Daphnia  
Duration: 24 hours  
Test: EC50  
Result: 9714 mg/l ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol  
Species: Crustacean  
Duration: 18 hours  
Test: EC10  
Result: 5175 mg/l ·

Product/substance propan-2-ol;isopropyl alcohol;isopropanol  
Species: Crustacean  
Duration: No data available.  
Test: EC50  
Result: >1000mg/l ·

## 12.2. ▼ Persistence and degradability

Product/substance ethanol  
Conclusion: Readily biodegradable

Product/substance propan-2-ol;isopropyl alcohol;isopropanol  
Result: 95%  
Conclusion: Readily biodegradable  
Test: OECD 301 E



## 12.3. Bioaccumulative potential

Product/substance: ethanol  
Conclusion: No potential for bioaccumulation

Product/substance: propan-2-ol;isopropyl alcohol;isopropanol  
Conclusion: No potential for bioaccumulation

Product/substance: carbon dioxide  
LogKow: 0,8300  
Conclusion: No potential for bioaccumulation

## 12.4. Mobility in soil

No data available.

## 12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

## 12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

## 12.7. Other adverse effects

None known.

## SECTION 13: Disposal considerations

### 13.1. ▼ Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*)  
To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

Dispose of contents/container to an approved waste disposal plant.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

#### ▼ EWC code

16 05 04\* Gases in pressure containers (including halons) containing dangerous substances


### Specific labelling



Not applicable.

### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information .
IMDG	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F	-	No	Limited quantities: 1 L EmS: F-D S-

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
					U See below for additional information .
IATA	UN1950 AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information .

\* Packing group

\*\* Environmental hazards

#### ▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

No specific requirements.

#### SEVESO - Categories / dangerous substances

P3b - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 5.000 tonnes (net) / (upper-tier): 50.000 tonnes (net)

#### ▼ REACH, Annex XVII

ethanol is subject to REACH restrictions (entry 40).

propan-2-ol;isopropyl alcohol;isopropanol is subject to REACH restrictions (entry 40).

#### Additional information

Not applicable.

#### ▼ Sources

The Danish Working Environment Authority's executive order no. 1049 of 30 May 2021 on young people's work. Based on Council Directive 94/33 / EC of 22 June 1994 on the protection of young people at work.

Pregnant workers and workers who are breastfeeding (AT Guide A.1.8-6, amended 2020).

Executive Order no. 247 of 14 March 2014 on interior design, etc. of aerosols, as amended by EO No. 301 of 27 March 2014, EO no. 478 of 25 May 2016 and EO 1336 of 29 November 2017.

Executive Order no. 372 of 25 April 2016 on control of the risk of major accidents with dangerous substances.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the

Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

## 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.  
H280, Contains gas under pressure; may explode if heated.  
H319, Causes serious eye irritation.  
H336, May cause drowsiness or dizziness.

#### The full text of identified uses as mentioned in section 1

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
LCS "C" = Consumer uses: Private households (= general public = consumers)  
PC 35 = Washing and Cleaning Products (including solvent based products)  
ERC 8a = Wide dispersive indoor use of processing aids in open systems

#### ▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne (European conformity)  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
GWP = Global warming potential  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### ▼ Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).  
The classification of the mixture in regard to physical hazards has been based on experimental data.

#### The safety data sheet is validated by

Lisbet Tetsche

#### ▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en