

P-30N SAFETY HARNESS

CE 1437 conforms to EN 361:2002

Ref.: AB 131 01

Full body harness P-30N is a component of personal protective equipment against falls from a height and conforms to EN 361.

Full body harness P-30N is recommended to use performing hot works like welding, grinding, soldering, metal cutting. Harness P-30N is manufactured of flame resistant materials. Harness P-30N is equipped with frontal and dorsal attachment point.

All straps (legs and shoulders) of the harness are adjustable by metallic buckles.

Static strength of frontal and dorsal attachment point is 15 kN (upward direction) and 10 kN (downward direction).

Full body harness P-30N can be used in temperatures from -30°C to +50°C

Materials:

- ARAMIDE fibres - 45 mm width webbing*
- NOMEX - threads*

*) The breaking tenacity of the synthetic fibres are at least 0,6 N/tex

- Zinc-plated - steel buckles
- Polyethylene - crossing plate and loops

Sizes:

size	height [cm]	chest girth [cm]
M-XL	164 - 180	85 - 100
XXL	180 - 195	100 - 130

Harness weight:

- M-XL - 1000g
- XXL - 1060g

dorsal attachment point (steel D-ring) with lengthening strap

regulating buckle

front attachment point (front loops connected with steel oval connector)

connecting and adjusting buckle

