

BANDIDO

AN INEXPENSIVE MODEL FOR GENUINE PROTECTION

Made entirely of highly-resistant polycarbonate, BANDIDO is the perfect value option.



BANCI



BANESP



BANPSF



BANPSJ



BANWPCC5



28 g

SUPPLIED WITH

Adjustable cord except for welding versions
CORDC


















+ WRAP-AROUND FIT

bollé
SAFETY

BANDIDO

AN INEXPENSIVE MODEL FOR GENUINE PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
BANDIDO	 Clear	BANCI	2C-1,2  1 FT €€	 EN166 FT €€	Anti-scratch/Anti-fog
	 ESP	BANESP	5-1,4  1 FT €€	 EN166 FT €€	Anti-scratch
	 Smoke	BANPSF	5-2,5  1 FT €€	 EN166 FT €€	Anti-scratch/Anti-fog
	 Yellow	BANPSJ	2C-1,2  1 FT €€	 EN166 FT €€	Anti-scratch/Anti-fog
	 Shade 5	BANWPC5	5  1 FT €€	 EN166 FT €€	Anti-scratch

LENS MARKING


Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

€€ European standard  Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

B-ESP

ESP, Extra Sensory Perception.
An innovative coating to reduce dazzle and the harmful affects of blue light.
B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE					
	BANCI	BANESP	BANPSF	BANPSJ	BANWPC5
Individual plastic bag	3660740002831	3660740003609	3660740003616	3660740003623	3660740003395
10 safety spectacles per inner box	3660740102838	3660740103606	3660740103613	3660740103620	3660740103392
240 safety spectacles per outer pack	3660740202835	3660740203603	3660740203610	3660740203627	3660740203399

CHARACTERISTICS	
LENSES	PC - 2,6 mm - Curve 9,25
FRAME	PC
TEMPLES	PC
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY