

HUSTLER

COMBINING STYLE AND PROTECTION

Water-repellent, the blue flash polarised version repels heat, providing optimum protection and reducing glare. Ideal for off-shore activities. Also available in a smoke version.



HUSTPSF



HUSTFLASH



HUSTPOL



31 g

SUPPLIED WITH

Microfibre pouch
ETUIFS















- + SIDE SHIELDS**
- + NON-SLIP BRIDGE**
- + NON-SLIP TEMPLES**

bollé
SAFETY

HUSTLER

COMBINING STYLE AND PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
HUSTLER	 Smoke	HUSTPSF	5-3,1  1 FT  €€	 EN166 FT €€	Anti-scratch/anti-fog
	 Polarized Blue flash	HUSTFLASH	5-3,1  1 FT  €€	 EN166 FT €€	Anti-scratch/anti-fog
	 Polarized	HUSTPOL	5-3,1  1 FT  €€	 EN166 FT €€	Anti-scratch/anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

€€ European standard  Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

B POLARIZED

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE			
	HUSTPSF	HUSTFLASH	HUSTPOL
Individual plastic bag	3660740006594	3660740006600	3660740007348
10 safety spectacles per inner box	3660740106591	3660740106607	36607400107345
240 safety spectacles per outer pack	3660740206598	3660740206604	3660740207342

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
TEMPLES	Nylon + insert EVA
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



01/10/2013

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY