

FUSION+

A COMBINATION OF PERFORMANCE, SAFETY AND STYLE

Inspired by the best assets of its predecessors, FUSION+ brings fantastic optical performance and greater comfort to the range.

Suitable for all welding, FUSION+ is the very essence of innovation.

Fusion+



538 g

SUPPLIED WITH

- Variable shades filter 5-8 / 9-13
- Adjustable headband
- Screen guards

TYPE

- Electro-optical filter

SPARE PARTS AVAILABLE

- Inner and outer screen guards
- Adjustable headband
- Sweatband

+ LOW BATTERY SIGNAL & CHANGEABLE BATTERY

+ VARIABLE SHADES 5-8/9-13

+ REACTION TIME: 0.10 MS

+ UV AND IR PROTECTION

+ 4 INDEPENDENT SENSORS

+ 100 X 53 MM FIELD OF VISION

+ TWO YEAR WARRANTY

bolle
SAFETY

FUSION+

A COMBINATION OF PERFORMANCE, SAFETY AND STYLE

| MODEL | REFERENCES | DESCRIPTION | WEIGHT | NORMS |
|----------------------------------|------------|---|--------|-------------|
| FUSION+ Variable Shade | FUSV | Electro-optical helmet with: | 538 g | EN379/EN175 |
| | | • B7VP Electro-optical filter with variable shades 5-8 / 9-13 | | EN379 |
| | | • Adjustable headband | | CE |
| | B7VP | Electro-optical filter with variable shades 5-8 / 9-13 | 148 g | EN379 |
| | COVFUSPEXT | 115 x 104 mm outer screen guard | 7 g | EN166 |
| | COVFUSPINT | 105 x 58 mm inner screen guard | 15 g | EN166 |
| | STFUSP | Adjustable headband | 115 g | CE |
| BESM | Sweatband | 3 g | CE | |

NORMS

EN175, standard for helmets

EN175 is the European standard that specifies the requirements and test methods related to personal protective equipment used to protect the operator's eyes and face from harmful optical radiation and other specific risks due to regular welding or cutting processes or other associated techniques. The standard specifies protection, including ergonomic aspects, against various risks or hazards including radiation, fire, mechanical and electrical risks. This standard defines the terms used and specifies the requirements related to materials, design and manufacture.

EN379, standard for filters

The specifications of the standard apply if such a filter is used for continuous observation of the welding process and if it is only used during the period when the arc is struck.

Bollé Safety product approval certificates to CE standards will be sent on request.

Electro-optical filter B7VP

| | |
|-----------------|-------------|
| DIMENSION | 110 x 90 mm |
| LENS THICKNESS | 10 mm |
| FIELD OF VISION | 100 x 53 mm |
| SENSORS | 4 |



Sensors

| | |
|----------------|---------------------------------------|
| SENSORS | 4 independent photoelectric detectors |
| POWER SUPPLY | solar energy |
| CLEAR STATE | Level DIN 4 |
| DARKENED STATE | Level DIN 5-8/9-13 |
| REACTION TIME | 0.10 ms |



CHARACTERISTICS

| | |
|-------------|---|
| USES | Coated electrodes, MIG / MAG, TIG, PLASMA, grinding |
| CONFORMS TO | EN379 / EN175 - UV et IR protection - permanent DIN16 |
| WARRANTY | 2 years |

Markings B7VP

| | | | | | | | |
|--|---|-----------------|--|---|--|-----------------|---------------------------|
| 4/5-8 / 9-13 |  | 1 / 1 / 1 / 2 / | EN 379 |  | | | |
| Scale number of the clear state / darkened state | Identification of the manufacturer Bollé Safety | Optical Class | Class number of the diffusion of the light | Class number of the variations in luminous transmittance class | Class number of the angle dependence of luminous transmittance | Standard number | European Community Symbol |

Markings for the helmet

| | | | |
|---|---|------------------|---|
|  | EN 175 | B |  |
| Identification of the manufacturer Bollé Safety | Reference standard about equipment for electric welding | Minimum Strength | European Community Symbol |

PACKAGING AND EAN13 CODE

| FUSV | B7VP | COVFUSPEXT | COVFUSPINT | STFUSP | BESM |
|---------------------------|---------------------------|-------------------------|-------------------------|-------------------------|------------------------|
| 3660740005696 per unit | 3660740005702 per unit | 3660740006440 per 10 | 3660740006457 per 10 | 3660740006471 per 10 | 3660740004569 per 5 |



Non-contractual pictures
24/11/2014

Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle-safety.com

bolle
SAFETY