

TECHNICAL DATASHEET

PRO 2000 CF22 A2P3 COMBINED FILTER



DESCRIPTION	
Part Number	5042670
Shelf Life	5 years factory sealed
Package	20
Storage Conditions	-10 °C + 50 °C (factory sealed)
Diameter	110mm
Height	95mm
Weight	241g
Connection	40 mm thread
Body Material	Polypropylene, reinforced

APPROVAL	
EN14387:2004	

PRO 2000 CF22 A2P3 COMBINED FILTER PROTECTS AGAINST:

A	A = Gases and vapours from organic compounds with a boiling point above 65°C
P3	P3 = Solid and liquid particles, toxic and radioactive particles, micro-organisms (e.g. bacteria and viruses). And enzymes
R	R = Reusable

TECHNICAL DATA

	PRO 2000 CF22 A2P3	EN14387:2004 Requirements
BREATHING RESISTANCE		
30 l/m	1.1 mbar	Max 2.6 mbar
95 l/m	3.7 mbar	Max 9.8mbar
GAS FILTER CAPACITY WITH TEST GAS @ 30 L/M		
Tetrachloromethane CCl ₄ (0.5 vol.-%)	58 min	Min 40 min
Cyclohexan C ₆ H ₁₂ (0.5 vol.-%)	50 min	Min 35 min
PARTICLE FILTER EFFICIENCY @ 95 L/MIN		
Sodium chloride NaCl (S)	<0.001%	Max 0.05%
Paraffin oil (L)	<0.003%	Max 0.05%