

INDUSTRIAL VACUUM CLEANERS

2 PEAR



SKY 250/500 - Oil Mist Collectors - OIL AND CHIPS







SUCTION UNIT					
Voltage	V - Hz	400 - 50			
Power	kW	0,12 - 0,18			
Max air flow	m³/h	250 - 500			
Suction inlet	mm	100			
Noise level (EN ISO 3744)	dB(A)	62			

FILTER UNIT			
Filter Type		Cartridge	
Surface - Diameter	cm²-mm	20.000	
Material - Efficiency	IEC 60335-2-69	M - PTFE	
Cartridge number		1	

VOLUME				
Dimensions	cm	39x47h		
Weight	kg	17 - 18		

- ✓ Compact, powerful and light.
- ✓ Reduced electrical consumption
- \checkmark Easy and fast maintenance.

- ✓ Easy mount on the machine.
- \checkmark Quick and easy filter replacement system.





SUCTION UNIT

The suction unit is a low power turbine with high air flow.



FILTER UNIT

Filtration versatility: multilayer filter (standard) or pleated high-surface filter cartridge with coalescent pre-filter



COLLECTION UNIT

The extracted and filtered oils and emulsions are thickened on the wall of the vacuum cleaner allowing recovery by drainage pipe.



OPTIONALS

- ✓ Painted metal kit for Air outlet fan
- ✓ Installation kit with riser.
- ✓ Installation kit with adjustable riser.
- ✓ Wall mounting kit.
- ✓ Column stand adjustable from 1.5 to 2.5 meters for fixing to the floor.
- ✓ Kit Cyclon Pre-filter