

INDUSTRIAL VACUUM CLEANERS





W 2 - Single phase industrial vacuum cleaner - INDUSTRIAL SINGLE PHASE









✓ Accessories included. Ideal for cleaning contractors.

100% stell construction. Suitable for wet and dry service, also simultaneously. Detachable container with direct bagging option.

SUCTION UNIT			
Voltage	V - Hz	230 - 50	
Power	kW	2 x 1,1	
Max waterlift	mmH2O	2400	
Max air flow	m³/h	360	
Suction inlet	mm	50	

FILTER UNIT			
Filter Type		Star	
Surface - Diameter	cm²-mm	20000	
Cleaning system		Manual	

COLLECTION UNIT		
Collection tank		Steel
Discharge system		Roll-out container
Capacity	lt.	40

VOLUME		
Dimensions	cm	55 x 63 x 115h





SUCTION UNIT

Suction is developed by two carbon brushes by-pass motors which are activated by independent switches placed on a solid, metallic head. Special noise buffers reduce the noise within the safety work standards.



FILTER UNIT

The polyester star filter with large filtration surface placed inside the filter chamber ensures protection from dust and avoids filter clogging.

The filter is cleaned mechanically by means of a manual filter shaking lever which shakes the filter vertically, ensuring safe and effective cleaning. This contributes to maintain high suction efficiency and avoids the spreading of dust in the environment.



COLLECTION UNIT

Suctioned material deposits inside an extractable stainless steel container fitted with wheels, allowing practical and safe emptying. Use with disposable bags is possible.



OPTIONALS

- ✓ Absolute Hepa filter H14
- ✓ Accessory basket
- ✓ Class M filter
- ✓ PTFE coated class M filter
- ✓ Class M teflon hydro-oleophobic filter
- ✓ Antistatic class L filter
- ✓ Antistatic class M filter
- ✓ Stainless steel collection tank and filter chamber
- ✓ Remote control electronic system
- ✓ Earth grounding